# **Delo<sup>®</sup> Bumper-to-Bumper Protection for Oilfield Trucks**





#### Fifth Wheel

Delo Grease ESI®EP 2 Delo Heavy Duty EP Delo Heavy Duty Moly 3% EP





# **Stationary Engine Coolant System**

Delo ELC Antifreeze/Coolant Delo XLC Antifreeze/Coolant HDAX® ELC Premixed 40/60





 ⊕ Delo 400 XSP SAE 5W-40 Delo 400 XLE SAE 15W-40



#### **Power End**

Delo Syn-Gear XDM SAE 75W-90 Delo Gear ESI SAE 80W-90



## Wheel Bearings

Delo Svn-Grease™ SFE EP 0





### **Truck Engine**

■Delo 400 XSP SAE 5W-40

Delo 400 XLE SAE 15W-40



(Allison 5000-9000 Series)

- Delo 400 XSP SAE 5W-40
- Delo 400 XLE SAE 15W-40





## **Truck Coolant System**

Delo ELC Antifreeze/Coolant Delo XLC Antifreeze/Coolant HDAX ELC Premixed 40/60



# **Clutch Bearings**

Delo Grease ESI®EP 2 Delo Grease ESI HD EP

**Truck Transmissions (Manual & Automatic)** 

Delo Syn-Trans XE SAE 75W-90 (AMT) Delo Syn-Trans HD SAE 50 (Manual) Delo Trans ESI SAE 40 (Manual)

Delo Syn ATF HD Delo Syn-Trans XV SAE 75W-80





**Differentials & Axles** Delo Syn-Gear XDM SAE 75W-90 Delo Syn-Gear HD SAE 75W-90 Delo Gear ESI SAE 80W-90



The product recommendations provide general guidelines for use in oilfield trucks. All manufacturers have different coolant and lubricant requirements and recommendations. It will be important to contact a Chevron representative or refer to the Original Equipment Manufacturer manual to confirm the proper product is used for the application. Visit chevron-gsc.force.com/lubeteksupport for confirmation of specific OEM specifications.





Delo®